

Homax®

Wall Texture

PRO GRADE KNOCKDOWN

Textura para pared

Light • up to 75 sq. ft.

Heavy • up to 35 sq. ft.

HOPPER GUN CONTROL™
Pressure & Spray Tip Adjustment

Delivers an Invisible Repair™
No Prime, Low Odor Formula
Heavy-Bodied

DANGER! FLAMMABLE VAPOR. CONTENTS UNDER PRESSURE.
CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
Read other cautions on side/back panel before using.

NET WT 25 OZ
(709 g)

WATER BASED BASE DE AGUA

Homax® Pro Grade Wall Texture with Dual Control Technology is the latest innovation in aerosol textures. This professional tool features adjustment of both pressure and pattern—similar to that of a gun and hopper; making this product convenient and simple to use without the hassle of mixing or using a compressor. The heavy-bodied, Knockdown formula is tinted for improved visibility during application and the no prime feature saves the Pro time. Simply spray, "knock down" with a mud knife and paint to achieve an invisible repair.



Watch a How-to Video at homaxproducts.com or scan this code to watch now!


For all Video Instructions or Homax® Products, e-mail us at info@homaxproducts.com or visit our website.

READ AND FOLLOW ALL WARNINGS AND PRECAUTIONS. PROTECT SURROUNDING AREA FROM OVERSPRAY. DO NOT SPRAY ON CLOTHING, FURNITURE OR CARPET.

DIRECTIONS FOR USE: MAKE NECESSARY WALL REPAIRS BEFORE APPLYING. SPOT PRIME REPAIR AREA BEFORE TEXTURE APPLICATION TO ENSURE BEST RESULTS. Priming after texture application is no longer needed. Always practice spraying on cardboard or scrap drywall to determine preferred pattern.

- 1. SHAKE CAN upside-down vigorously for one full minute before using and continuously during use.**
- 2. REMOVE safety tab from top of trigger. REMOVE red clip from below pressure toggle. REDRAW red dip and reattach for storage.**
- 3. ADJUST PATTERN:** POINTING AWAY FROM FACE, TURN YELLOW SPRAY TIP TO DESIRED PATTERN: STRAIGHT UP FOR LIGHT KNOCKDOWN, COUNTER CLOCKWISE for HEAVY KNOCKDOWN
- 4. ADJUST PRESSURE:** MOVE YELLOW TOGGLE: RIGHT for HIGH, LEFT for LOW
"As contents and pressure in can decrease, adjust pressure and pattern to maintain a consistent texture appearance."
- 5. SPRAY 6"-18"** from the wall using a circular just sweeping motion and working in 4' x 4' sections. Note: Depending upon PRESSURE & PATTERN settings, distance may vary. Sprays best between 70-80°F. Apply in random pattern, covering only 70-80% of surface. Shake can occasionally throughout use.
- 6. KNOCK DOWN:** Allow texture to dry no more than 1-2 minutes before LIGHTLY KNOCKING DOWN OR FLATTENING using a 6-8" wet drywall knife. For best results, hold knife almost parallel to the wall. If knife drags, shorten dry time. Texture can be scraped off and reapplied when wet until desired pattern is achieved. DRY TIME: Allow to dry 60 minutes before painting. Heavier textures may require longer dry time, dependent upon temperature and humidity.
- CLEAN-UP:** Warm water
- AFTER USE TO STORE:** clear nozzle by turning can upside down, move toggle to high pressure and spray until texture is cleared. Retract red clip under pressure toggle for storage.
- PAINT** with 2 coats or more for complete hide and to match gloss (dependent upon color and paint manufacturer's instructions).

DANGER! FLAMMABLE VAPOR. CONTENTS UNDER PRESSURE. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. Contains Calcium Carbonate, Talc, Hexylene Glycol, Vinyl Acrylic Copolymer, Quartz, and Dimethyl Ether (propellant). Vapors may catch fire. Keep away from heat, sparks and flame. Extinguish all flames and sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Store upright in a cool, dry place. Avoid prolonged exposure to sunlight and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Use with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with eyes and skin. Wear safety glasses or goggles. Wash hands after using. **FIRST AID:** For eye contact, flush thoroughly with water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. If inhaled, remove person to fresh air. If breathing does not improve, get medical attention. **KEEP OUT OF REACH OF CHILDREN. WARNING:** This product contains a chemical known to the State of California to cause cancer. **WARNING:** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



- 1. ANTE LA LATA** al usar vigorosamente por un minuto completo, y continuamente durante el uso.
- 2. RETIRAR** la lengüeta de seguridad de punta del gatillo. RETIRAR el clip rojo del interruptor debajo del interruptor de presión. RETIRAR el clip rojo y volver a colocarlo en su posición.
- 3. AJUSTAR EL PATRÓN:** APUNTANDO LEJOS DE SU CARA, GIRE LA BOBILA ROTATORIA Hacia LA LA POSICIÓN DESEADA. PUNTEO EN LINEA RECTA PARA PATRÓN DESEADO. GIRE EN SENTIDO DE LAS AGUJAS PARA PATRÓN DESEADO.
- 4. AJUSTAR LA PRESIÓN:** MUEVA EL INTERRUPTOR AMARILLO. AJUSTE SPRAY AL DESEADO. Spraying a desired pattern requires spraying on cardboard or scrap drywall to determine preferred pattern.
- 5. MOVER** a una distancia de 15.24 cm a 45.72 cm de la pared con un movimiento de barrido. Nota: Según las condiciones de temperatura y humedad, la distancia puede variar. Aplicar en patrón aleatorio, cubriendo solo el 70% a 80% de la superficie. Agitar ocasionalmente la lata.
- 6. BATER** LA LATA: Solo que la textura se seque de 1 a 2 minutos antes de BATER LA LATA. Utilizar una espátula para planear la textura. Nota: Dependiendo de las condiciones de temperatura y humedad, el tiempo de secado puede variar. La textura puede ser raspada y reaplicada cuando esté húmeda hasta que se logre el patrón deseado.
- 7. LIMPIAR** LA LATA: Limpia la boquilla de la lata al guardar la lata. Retraer el clip rojo debajo del interruptor de presión para almacenar la lata.
- 8. DESPUÉS DE USAR Y PARA ALMACENAR EL PRODUCTO:** Limpia la boquilla de la lata al guardar la lata. Retraer el clip rojo debajo del interruptor de presión para almacenar la lata.
- 9. PAINT** with 2 coats or more for complete hide and to match gloss (dependent upon color and paint manufacturer's instructions).

PRECAUTIONS: Los vapores pueden provocar irritación. Mantener alejado del calor, chispas y flamas. Evitar la exposición a los vapores y flamas de ignición durante su uso y hasta que los vapores de ignición dejen de salir. Evitar los vapores de ignición dejen de salir. Evitar la acumulación de vapores obteniendo todos los ventiladores y puertas para obtener ventilación cruzada. Puede provocar daños neurológicos en bebés y niños, los efectos pueden ser permanentes. Puede provocar mareos, náuseas o fatiga. Usar con precaución con ventilación adecuada. Evitar respirar el vapor y la bruma de la pulverización. Evitar el contacto con los ojos y la piel. Usar gafas protectoras o gafas y guantes de seguridad. Un respirador adecuado y debidamente calibrado aprobado por el NIOSH puede brindar protección adicional, pero se debe utilizar solamente de acuerdo con las instrucciones del fabricante para el uso del respirador. No perforar ni incinerar (quemar) el envase. No exponer al calor ni almacenar a temperaturas que superen los 46°C (115°F). Evitar la exposición prolongada al sol o al calor de radiadores, estufas, agua caliente u otras fuentes de calor que puedan provocar explosión.

Flat Paint Product VOC < 60% PWBW < 1.20
Paints & Primers
Homax® A Premier Brand of The Homax Group, Inc.
Bellingham WA 98227
www.homaxproducts.com
800-720-0020
MADE IN USA
400-22361-304-2

0 41072 04565 0